

# แบบกันรถโฆษณาอัตโนมัติ

## ADVERTISEMENT BARRIER GATE

**DPARK**

# CD 806

### INTRODUCTION:


New media for vehicle entrance and exit.

### SPECIFICATION:

1. Power Supply: 220V+10%/50HZ 110V+10%/60HZ
2. Motor Power: 140W
3. Temperature: -30 degree to 80 degrees
4. Related Humidity: <=95%
5. Barrier Body Dimension: 450mm\*800mm\*1245mm
5. Boom Length: No more than 3.7 meters
6. Advertising Boom Board Dimension: 92\*830mm
7. Barrier Body Advertisement Plate Dimension: 450\*880mm
8. LED Light: 15A, 200w
9. Total Height for Boom Lift: Decided by boom length
10. Boom Lifting Time: 5s
11. Top Tube Middle line Height: 1050mm
12. Remote Control Distance: <=30m
13. Input Interface: +12V Level Signal or more than 100ms impulse  
Driving current less than 10mA
14. Communication Interface: RS485



### VIEWS:



Model	Boom Lifting Time (Second)	Boom Length(Meters) L1	Advertisement Plate Numbers	Advertisement Dimension L2
ST806	5s	3.2m	29 Pieces	2730*830mm
	5s	3.7m	34 Pieces	3200*830mm
	8s	4.2m	39 Pieces	3670*830mm